

Product Bulletin

Astound

High Strength Engine Degreaser

A premium quality, water-based detergent designed for cleaning engines, transmissions and other automotive parts and equipment. Contains a powerful blend of solvents, alkalis and surfactants for unsurpassed cleaning performance. May also be used for degreasing ferrous metals (iron and steel), machinery, equipment, walls, floors, and any other area where troublesome grease and soil must be removed. Ideal for use in steam cleaners or pressure washing equipment. Not recommended for use on glass, magnesium or aluminum surfaces. Leaves engines and parts thoroughly clean. Highly dilutable and economical to use.

Directions for Use

Prior to use, test this product in an inconspicuous area to assure compatibility with surface. For pressure washing, dilute **Astound** at a feed rate of 30-50:1, depending on soil level and water hardness. Apply at low pressure to dry surface—do not pre-wet. Allow solution several minutes to penetrate and dissolve soils. Do not allow to dry on surface, especially glass, magnesium or aluminum. Rinse surfaces thoroughly with hot, high pressure water (1,500 psi or better). Avoid use in direct sunlight.

Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Yellow-green Liquid
Odor	Characteristic
Alkalinity (as NaOH)	High
pH (1% solution)	>12.0
Foaming	High
Flash Point	>200°F
Bulk Density	approx. 9.00 lbs./gal.
Solubility in Water	100%
Rinsing	Good
Chlorine Content	None
Phosphorous as P ₂ O ₅	None
Hard Water Performance	Good
Freeze/Thaw Stability	Moderate

Package Size

Product Code

4x1 gal. case	#88041
5 gal. pail	#88005
55 gal. drum	#88055