

Product Bulletin

Breakdown

Premium Performance Wax Stripper

Super-strength floor finish remover for use by professional maintenance personnel. **Breakdown** contains powerful alkalis and solvents for fast, complete stripping of all types of floor finishes and waxes. Reduces stripping time considerably, producing labor and cost savings. Non-ammoniated. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, etc.

Directions for Use

Before use, pretest this product in an inconspicuous area to assure compatibility with surface. **Breakdown** may be used at variable dilution rates depending on the type of finish to be removed and the desired removal time. Dilute 4-32 ounces per gallon of hot water according to the requirements of the particular application. Apply solution liberally to the floor and allow several minutes dwell time to penetrate and dissolve finish. Agitate with a scrubbing pad to facilitate removal. Pick up solution with a mop or wet-dry vacuum. Rinse floor completely with clean water and allow to dry before reapplying finish.

Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Yellow-Green Liquid
Odor	Characteristic
Alkalinity (as NaOH)	High
pH (1% solution)	>12.0
Foaming	Moderate
Flash Point	>200°F
Bulk Density	approx. 9.09 lbs./gal.
Solubility in Water	100%
Solvency	High
Chlorine Content	None
Phosphorous as P ₂ O ₅	None
Hard Water Performance	Good
Freeze/Thaw Stability	Complete

Package Size

Product Code

4x1 gal. case	#42141
5 gal. pail	#42105
55 gal. drum	#42155