

## Product Bulletin

# Endurance™

## High Performance Floor Finish

A hard, 18% solids floor finish designed for repeated scrubbing and buffing on resilient tile floors. Provides excellent gloss and improved durability over standard finishes. **Endurance** contains a metal interlock, high performance polymer which forms a clear, tough, long-wearing shine. Recommended for use on floors made of linoleum, vinyl, asbestos, terrazzo, rubber, concrete, sealed wood and unglazed ceramic. May be used as a first coat sealer. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, etc.

### Directions for Use

Before use, pretest this product in an inconspicuous area to assure compatibility with surface. Strip old finish from floor, rinse completely and allow to air dry. Apply **Endurance** in thin, even coats using a rayon mop or lambs wool pad. For optimum gloss and durability, apply 5 coats or more, allowing at least 30 minutes drying time between coats. Floor may be machine buffed to a higher gloss if desired. Coverage = approximately 2,500 sq. ft./gal.

### Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



### Technical Specifications

Appearance	Opaque White Liquid
Odor	Characteristic
Alkalinity (as NaOH)	None
pH (1% solution)	<9.0
Foaming	None
Flash Point	>200°F
Bulk Density	approx. 8.53 lbs./gal.
Solubility in Water	100%
Solids Content	18%
Chlorine Content	None
Phosphorous as P <sub>2</sub> O <sub>5</sub>	None
Hard Water Performance	NA
Freeze/Thaw Stability	Complete

### Package Size      Product Code

4x1 gal. case	#43741
5 gal. pail	#43705
55 gal. drum	#43755