

Product Bulletin

Hustle

Pressure Wash and Steam Cleaner

Professional quality pressure wash detergent for removing dirt and grime from all types of industrial surfaces, including walls, equipment, floors, machinery, etc. Contains a very powerful blend of solvents, surfactants, and alkalis in addition to special emulsifiers for rapid soil penetration and removal. Produces abundant foam for increased dwell time on vertical surfaces. An ideal product for most pressure washing applications. Designed to deliver effective performance where other products fail. Highly dilutable and economical to use.

Directions for Use

Prior to use, test product in an inconspicuous area to assure compatibility with surface. Wear appropriate safety equipment at all times.

Pressure Washing: Using low pressure, apply this product at a feed rate of 2-8 ounces per gallon of hot water (16-64:1) depending on soil levels. For best results, apply to a dry surface--do not prewet. Work from the bottom up until all surfaces are thoroughly coated with detergent solution. Allow several minutes contact time for detergent to penetrate and dissolve soils. Using hot water under high pressure (1,000 psi or higher), rinse surface completely. Do not allow solutions to dry on surface. For spot removal or very heavy grease or soil accumulation, use at full strength.

Manual Washing: For brush and bucket washing, dilute this product at 1-2 ounces per gallon of hot water (60-100:1). Apply using a mop, sponge or scrub brush. Allow several minutes contact time. Agitate to improve soil removal, then rinse completely.

Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Blue Liquid
Odor	Characteristic
Alkalinity (as NaOH)	Very High
pH (1% solution)	>12.0
Foaming	High
Flash Point	>200°F
Bulk Density	approx. 9.10 lbs./gal.
Solubility in Water	100%
Rinsing	Good
DOT Classification	Corrosive
Phosphorous as P ₂ O ₅	None
Hard Water Performance	Good
Freeze/Thaw Stability	Do Not Freeze

Package Size Product Code

55 gal. drum

91255