

Product Bulletin

JetStream™

Premium Foaming Auto Presoak

A professional quality product for removing road film and soil buildup from automotive and other hard surfaces. Produces abundant foam for increased contact time on vertical surfaces, while special builders, surfactants and solvents lift dirt and grime away. Ideal for use in self serve and touchless automatic car washes, or with portable pressure washing equipment.

Directions for Use

Mixing Instructions: Dilute 13 ounces of this product per gallon of hot water (4 lbs. per 5 gal. pail, or 45 lbs. per 55 gal. drum). Mix vigorously for 10+ minutes until powder is completely dissolved. Longer mixing times will be required for warm or cold water, or for low agitation. Failure to completely mix this product may result in clogged injector tubes, spray hoses or spray nozzles. For a ready-to-use solution, dilute 18 oz. per 55 gallons of hot water.

Use Instructions: Using low pressure, apply prepared solution at a feed rate of 3-6 ounces per gallon of hot water (20-40:1). For best results, apply to a dry surface--do not prewet. Work from the bottom up until all surfaces are thoroughly coated with detergent solution. Allow a few minutes contact time for detergent to penetrate soils, but DO NOT allow solution to dry on vehicle surfaces, especially glass, aluminum or magnesium. Using hot water under high pressure (1,000 psi or higher), rinse surface completely.

Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

| | |
|--|------------------------|
| Appearance | White Powder |
| Odor | Characteristic |
| Alkalinity (as NaOH) | High |
| pH (1% solution) | >11.0 |
| Foaming | Very High |
| Flash Point | NA |
| Bulk Density | approx. 8.00 lbs./gal. |
| Solubility in Water | 100% |
| Rinsing | Excellent |
| Chlorine Content | None |
| Phosphorous as P ₂ O ₅ | >10.0% |
| Hard Water Performance | Very Good |
| Freeze/Thaw Stability | NA |

| Package Size | Product Code |
|--------------|--------------|
| 50 lb. drum | #81550 |
| 100 lb. drum | #81501 |
| 300 lb. drum | #81503 |