

Product Bulletin

LegacyTM *Ultra Performance All Speed Floor Finish*

An ultra-premium, all speed finish which provides unsurpassed gloss and durability on resilient tile floors. **Legacy** is a high solids finish which contains a metal interlock, multi-coatable polymer that forms a clear, tough, long-wearing shine. Recommended for use on floors made of linoleum, vinyl, asbestos, terrazzo, rubber, concrete, sealed wood and unglazed ceramic. Resists scuffs and heal marks. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, etc. Scrubbable and recoatable.

Directions for Use

Strip old finish, waxes and seals from floor. Rinse completely to remove chemical residues, then allow to air dry. Pretest this product in an inconspicuous area to assure compatibility with surface. Apply **Legacy** in thin, even coats using a rayon mop or lambs wool pad. For optimum gloss and durability, apply 5 coats or more, allowing at least 30 minutes drying time between coats. Floor may be machine buffed to a higher gloss if desired. Coverage = approximately 2,500 sq. ft./gal.

Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

Appearance	Opaque White Liquid
Odor	Characteristic
Alkalinity (as NaOH)	None
pH (1% solution)	<9.0
Foaming	None
Flash Point	>200°F
Bulk Density	approx. 8.63 lbs./gal.
Solubility in Water	100%
Solids Content	24%
Chlorine Content	None
Phosphorous as P ₂ O ₅	None
Hard Water Performance	NA
Freeze/Thaw Stability	Moderate

Package Size **Product Code**

4x1 gal. case	#43541
5 gal. pail	#43505
55 gal. drum	#43555