

## Product Bulletin

# PowerFoam

## *Touchless Automatic Vehicle Detergent*

Professional quality pressure wash detergent for removing road film and soil buildup from automotive and other surfaces. Produces abundant foam for increased dwell time on vertical surfaces, while builders and surfactants lift dirt and grime away. Formulated for use with pressure wash applications, especially in touchless automatic car washes. Very economical to use. Non-corrosive to metal surfaces. Cherry fragrance.

### Directions for Use

Dilute 8 ounces of this product per gallon of hot water. Consult product label for complete mixing instructions. Apply prepared solution at a feed rate of 2-4 ounces per gallon of water (30-60:1). For best results, apply solution to dry vehicle surface--do not prewet. Use hot (120° F or higher), softened water at 1,000 psi or more. Work from the bottom up until all surfaces are thoroughly coated with detergent solution. Allow several minutes contact time for detergent to penetrate and dissolve soils, then rinse surface completely. Do not allow solutions to dry on vehicle surface. Avoid use in direct sunlight.

### Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



### Technical Specifications

Appearance	Red Powder
Odor	Cherry
Alkalinity (as NaOH)	Moderate
pH (1% solution)	>10.0
Foaming	Very High
Flash Point	>NA
Bulk Density	approx. 8.00 lbs./gal.
Solubility in Water	100%
Rinsing	Excellent
Chlorine Content	None
Phosphorous as P <sub>2</sub> O <sub>5</sub>	<10.0%
Hard Water Performance	Excellent
Freeze/Thaw Stability	NA

### Package Size                      Product Code

50 lb. drum	#85750
100 lb. drum	#85701
300 lb. drum	#85703