

## Product Bulletin

# TerraSeal

## Acrylic Floor Sealer

A professional quality, semi-permanent base for sealing resilient tile floors. Provides a durable, acrylic base for conventional and high speed floor finishes. Fills pores in tile and grout while providing an initial gloss. Improves the performance and durability of all types of floor finishes. May be used on all types of resilient tile, concrete and terrazo. Non-yellowing. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, etc.

### Directions for Use

Before use, assure that the floor has been completely stripped of old finish and is clean, dry and free of any stripper residue. Apply **TerraSeal** in a thin, even coat using a rayon mop or lambs wool pad. Lay undiluted product evenly, covering all floor surfaces completely. Allow at least 30 minutes drying time before applying the first coat of finish. Coverage = approximately 1,500-2,500 sq. ft./gal. depending on the porosity of the floor.

### Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



### Technical Specifications

Appearance	Opaque White Liquid
Odor	Characteristic
Alkalinity (as NaOH)	None
pH (1% solution)	<9.0
Foaming	None
Flash Point	>200°F
Bulk Density	approx. 8.40 lbs./gal.
Solubility in Water	100%
Solids Content	>12%
Chlorine Content	None
Phosphorous as P <sub>2</sub> O <sub>5</sub>	None
Hard Water Performance	NA
Freeze/Thaw Stability	Moderate

### Package Size

### Product Code

4x1 gal. case	#44341
5 gal. pail	#44305
55 gal. drum	#44355