

Product Bulletin

Ultra Shine

Premium Performance Floor Finish

A premium quality all speed finish which provides excellent gloss and durability on resilient tile floors. **Ultra Shine** contains a metal interlock, multi-coatable polymer which forms a clear, tough, long-wearing shine. Recommended for use on floors made of linoleum, vinyl, asbestos, terrazzo, rubber, concrete, sealed wood and unglazed ceramic. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, etc.

Directions for Use

Before use, pretest this product in an inconspicuous area to assure compatibility with surface. Strip old finish from floor, rinse completely and allow to air dry. Apply **Ultra Shine** in thin, even coats using a rayon mop or lambs wool pad. For optimum gloss and durability, apply 5 coats or more, allowing at least 30 minutes drying time between coats. Floor may be machine buffed to a higher gloss if desired. Coverage = approximately 2,500 sq. ft./gal.

Safety Reminder

Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.



Technical Specifications

| | |
|--|------------------------|
| Appearance | Opaque White Liquid |
| Odor | Characteristic |
| Alkalinity (as NaOH) | None |
| pH (1% solution) | <9.0 |
| Foaming | None |
| Flash Point | >200°F |
| Bulk Density | approx. 8.53 lbs./gal. |
| Solubility in Water | 100% |
| Solids Content | 24% |
| Chlorine Content | None |
| Phosphorous as P ₂ O ₅ | None |
| Hard Water Performance | NA |
| Freeze/Thaw Stability | Moderate |

Package Size

Product Code

| | |
|---------------|--------|
| 4x1 gal. case | #43141 |
| 5 gal. pail | #43105 |
| 55 gal. drum | #43155 |