

CR∏WNTechnical Data Sheet

AUTOJET



Super-Concentrated Low pH High Foam Automotive Presoak

for Touchless and Friction Car Washes

A super-concentrated, high performance acidic detergent for use in car washes and pressure washing applications. Removes road film, salt, silt, clay, scale, dust, soot and other inorganic soils from automotive surfaces. Designed to be used in combination with an alkaline presoak as a two-part system for superb removal of organic and inorganic soils typically found on automotive surfaces. Very high foaming for increased contact time on vertical surfaces and improved cleaning performance. Contains a special blend of chelants, organic acids and foam additives for rapid soil penetration and emulsifying. Improves the performance of clear coat protectants and drying agents by removing soils, neutralizing alkalinity and reducing water spotting. Ideal for use in touchless and friction car washes as well as self-serve operations. May also be used with portable pressure washing equipment. Contains no Hydrofluoric Acid or Ammonium Bifluoride.

Directions for Use

This product is designed to be used in conjunction with an alkaline presoak as part of a two-component cleaning process. For best results, first apply a solution of this product to the vehicle surface through foaming equipment. Apply to dry surface - do not pre-wet. Use foaming equipment and spray nozzles and thoroughly coat all vehicle surfaces with detergent solution. For touchless operations, dilute at a rate of 75 - 110:1 (1.1 - 1.7 ounces per gallon). For friction operations, dilute at rate of 128 - 180:1 (.70 - 1.0 ounce per gallon). Follow promptly with an application of an alkaline presoak, again through foaming equipment and spray nozzles. Consult product label for dilution rates. Rinse completely with hot, high-pressure water (1,000 psi or higher). Follow with application of clear coat protectant, drying agent, etc. Do not allow solutions to dry on automotive surfaces.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance Odor pH (1% solution, 22°C) Foaming Flash Point Bulk Density (lbs/gal, 22°C) Stability Range Free Alkalinity (as Na₂O) Solubility (in H₂O, 22°C)

Product Number

Acid Type(s)

Pink Liquid Cherry <2.0 Very High None 9.24±0.1 50-100°F None 100% Phosphoric

Packaging

5 gal. pail 15 gal. drum 30 gal. drum 55 gal. drum



4701 W. 136th St. • Crestwood, IL 60418 tel (708) 371-6990 • (800) 672-4065 fax (708) 371-6992 www.crown-chem.com

