



CROWN™

Technical Data Sheet

BEAD & BREAK™



Polymer-Based Water Repellant for Superior Sheeting & Protection for Low & High Pressure Spray Applications

This product works on glass, paint, trim and chrome. Provides increased shine, water repellency and more durable protection. Contains special polymers which create a water-repellant layer that chemically bonds to vehicle surfaces. Reduces paint oxidation and dulling. Designed for low- or high-pressure spray applications. Contains no mineral seal oil or other hydrocarbons.

Directions for Use

The amount of this product to use will depend on several variables, including conveyor speed, temperature, spray area, etc. For optimum drying and waxing performance with minimum product waste, adjust proportioner as recommended by equipment manufacturer, or adjust metering device to give maximum results. For most applications, apply full strength at the rate of 128:1 - 170:1 (approximately 3/4 to 1 oz. per vehicle). Cold weather may require higher usage amounts.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.

Technical Specifications

Appearance	Green Liquid
Odor	Cherry
pH (1% solution, 22°C)	<9.0
Foaming	None
Flash Point	>200°F
Bulk Density (lbs/gal, 22°C)	8.33±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	None
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

84505
84515
84530
84555

Packaging

5 gal. pail
15 gal. drum
30 gal. drum
55 gal. drum



4701 W. 136th St. • Crestwood, IL 60418
tel (708) 371-6990 • (800) 672-4065
fax (708) 371-6992
www.crown-chem.com



★ MADE IN USA ★