

CRNWN[™] Technical Data Sheet

Big Rig[™]



High-Performance Foaming Alkaline Pressure Wash Detergent for Trucks and Commercial Vehicles

A professional quality product for removing grease, grime and soil from truck cabs and trailers, buses, automotive and most other hard surfaces. Produces abundant foam for increased contact time on vertical surfaces, while builders, surfactants and solvents lift dirt and grime away. Formulated for use with pressure washing equipment. Non-corrosive to metal and safe for use on all surfaces.

Directions for Use

Mixing Instructions: Dilute 13-16 ounces of this product per gallon of hot water (4-5 lbs. per 5 gallon pail; 44-55 lbs. per 55 gallon drum; or 220-275 lbs. per 275 gallon tote). Mix vigorously for 10+ minutes until powder is completely dissolved. Longer mixing times (up to 45 minutes) will be required for warm or cold water, or for low agitation. Failure to completely mix this product may result in clogged injector tubes, spray hoses or spray nozzles.

Use Instructions: Using low pressure, apply prepared solution at a feed rate of 2-4 ounces per gallon of hot water (30-60:1). For best results, apply to a dry surface-do not prewet. Work from the bottom up until all surfaces are thoroughly coated with detergent solution. Allow several minutes contact time for detergent to penetrate and dissolve soils. Using hot water under high pressure (1,000 psi or higher), rinse surface completely. Do not allow solutions to dry on surface.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance Odor pH (1% solution, 22°C) Foaming Flash Point Bulk Density (lbs/gal, 22°C) Stability Range Free Alkalinity (as Na₂O) Solubility (in H₂O, 22°C) Phosphate Content (as P)

Product Number

85950 85901 85903 White Powder Characteristic <12.0 Very High N/A 10.00±0.1 N/A Very High 100% <5.0%

Packaging

50 lb. drum 100 lb. drum 300 lb. drum



4701 W. 136th St. • Crestwood, IL 60418 tel (708) 371-6990 • (800) 672-4065 fax (708) 371-6992 www.crown-chem.com

