

BREAKDOWN™

Professional Strength Wax Stripper for Resilient Tile Floors

Super-strength floor finish stripper for use by professional maintenance personnel. Contains powerful alkalis and solvents for fast, complete stripping of all types of floor finishes and waxes. Reduces stripping time considerably, producing labor and cost savings. Non-ammoniated. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, etc.

Directions for Use

Before use, pretest this product in an inconspicuous area to assure compatibility with surface. May be used at variable dilution rates depending on the type of finish to be removed and the desired removal time. Dilute 4-32 ounces per gallon of hot water according to the requirements of the particular application. Apply solution liberally to the floor and allow several minutes dwell time to penetrate and dissolve finish. Agitate with a scrubbing pad to facilitate removal. Pick up solution with a mop or wet-dry vacuum. Rinse floor completely with clean water and allow to dry before reapplying finish.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's can be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	Yellow-Green Liquid
Odor	Characteristic
pH (1% solution, 22°C)	>11.5
Foaming	Moderate
Flash Point	None
Bulk Density (lbs/gal, 22°C)	9.09 ±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	High
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

42141
42105

Packaging

4x1 gal. case
5 gal. pail