



CROWN™

Technical Data Sheet

CRYSTAL DRY™



Clear Coat Protectant and Drying Agent with Silicone Wax for Friction and Touchless Car Washes

This product is a high-performance total body clear coat protectant and drying agent fortified with silicone wax. Provides outstanding beading performance and assures fast breaking of water off of car surface and better drying from blowers. Silicone wax chemically bonds to vehicle surfaces, improving shine, water repellency and durable protection. Treated vehicles exhibit beading and repellency much longer than standard drying agents. Helps protect vehicle undercarriage from salt and road grime. Reduces paint oxidation and dulling. Designed for low- or high-pressure spray applications in friction and touchless applications.

Directions for Use

The amount of this product to use will depend on several variables, including conveyor speed, temperature, spray area, etc. For optimum drying and waxing performance with minimum product waste, adjust proportioner as recommended by equipment manufacturer, or adjust metering device to give maximum results. For most applications, apply full strength at the rate of 128:1 - 170:1 (approximately 3/4 to 1 oz. per vehicle). Cold weather may require higher usage amounts.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.

Technical Specifications

Appearance	Orange Liquid
Odor	Characteristic
pH (1% solution, 22°C)	<9.0
Foaming	None
Flash Point	>200°F
Bulk Density (lbs/gal, 22°C)	8.13±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	None
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

84405
84415
84430
84455

Packaging

5 gal. pail
15 gal. drum
30 gal. drum
55 gal. drum