

FAT CHANCE™

High Foaming Degreaser for Meat Rooms and Food Plants

High strength detergent dissolves fat, oil, grease and food soils. High foaming for improved contact time and cleaning performance on vertical surfaces. Excellent for use with foaming equipment, pressure washers, floor scrubbers, soak and immersion cleaning, and manual cleaning processes. Formulated to provide powerful cleaning in meat rooms, meat processing and packing facilities, food processing plants, supermarket food preparation areas, butcher shops, delicatessens, and many other operations requiring exceptional performance. Contains a powerful blend of surfactants, solvents and alkalis for outstanding penetration and removal of built-up grease and fat. Highly concentrated and economical to use. Avoid contact with aluminum, galvanized metals, tin, pewter or painted surfaces.

Directions for Use

Foam Cleaning: Cover or remove all food products from area. Dilute this product at 4-12 ounces per gallon of hot water depending on the amount and type of soil to be removed. Follow manufacturer's instructions for using foam generating equipment. Apply foam solution to walls, floors, equipment and other surfaces to be cleaned. Allow foam to remain for 5-10 minutes to penetrate and dissolve soils. Do not allow foam to dry on surfaces; reapply as necessary to keep surfaces wet. Scrub with a nylon pad or brush to improve soil removal, particularly stubborn deposits. Rinse thoroughly with high pressure potable water. Allow surfaces to drain dry. Do not wipe dry. Sanitize surfaces with a no-rinse sanitizer.

Pressure Washing: Apply a solution of 4-12 ounces per gallon of water depending on the amount and type of soil to be removed. Follow manufacturer's instructions for using pressure washing equipment. Do not prewet surfaces with water. Apply detergent solution to dry surfaces, at low pressure, to walls, floors, equipment and other surfaces to be cleaned. Allow solution to remain for 5-10 minutes to penetrate and dissolve soils. Do not allow detergent to dry on surfaces; reapply as necessary to keep surfaces wet. Scrub with a nylon pad or brush to improve soil removal, particularly stubborn deposits. Rinse thoroughly with high pressure potable water. Allow surfaces to drain dry. Do not wipe dry. Sanitize surfaces with a no-rinse sanitizer.

Floor Scrubbers: Dilute 1-2 ounces of this product per gallon of hot water into the machine's solution tank. Follow manufacturer's instructions for using floor scrubbing equipment. Rinse floors with clean water and allow to dry before reuse.

Manual Cleaning: Dilute 2-6 ounces of this product per gallon of hot water in a mop bucket. Apply solution to surfaces to be cleaned using a mop or sponge. Allow 3-5 minutes contact time to penetrate and dissolve soils. Scrub with a nylon pad or brush to improve soil removal, particularly stubborn deposits. Rinse with clean water and allow to dry before reuse.

Soak and Immersion Cleaning: To clean stainless steel equipment, machinery, utensils, filters, parts, and other similar sized food processing items, preclean or prespray items to remove heavy soils. Immerse items in a solution of 4-8 ounces of this product per gallon of hot water. Heat solution to 120°F. Allow items to soak for 30-60 minutes depending on the type and amount of soil to be removed. Use circulation or agitation if available to improve cleaning performance. Remove items and rinse thoroughly with potable water. Allow items to drain dry. Do not wipe dry. Sanitize with a no-rinse sanitizer.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	Colorless Liquid
Odor	Characteristic
pH (1% solution, 22°C)	<11.5
Foaming	Very High
Flash Point	None
Bulk Density (lbs/gal, 22°C)	8.86 ±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	High
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

95805
95855

Packaging

5 gal. pail
55 gal. drum