



CROWN™

Technical Data Sheet

JETSTREAM™



Premium Powdered Alkaline Presoak & Pressure Wash Detergent for Friction & Touchless Car Washes

Highly effective detergent for removing road film and soil buildup from automotive and other hard surfaces. Produces abundant foam for increased contact time on vertical surfaces, while special builders, surfactants and solvents lift dirt and grime away. Ideal for use in self-serve and touchless automatic car washes or with portable pressure washing equipment.

Directions for Use

Mixing Instructions: Dilute 13 ounces of this product per gallon of hot water (4 lbs. per 5 gal. pail, or 45 lbs. per 55 gal. drum). Mix vigorously for at least 10 minutes until powder is completely dissolved. Longer mixing times will be required for warm or cold water, or for low agitation. Failure to completely mix this product may result in clogged injector tubes, spray hoses or spray nozzles. For a ready-to-use solution, dilute 18 oz. per 55 gallons of hot water.

Use Instructions: Using low pressure, apply prepared solution at a feed rate of 3-6 ounces per gallon of hot water (20-40:1). For best results, apply to a dry surface--do not prewet. Work from the bottom up until all surfaces are thoroughly coated with detergent solution. Allow a few minutes contact time for detergent to penetrate soils, but DO NOT allow solution to dry on vehicle surfaces, especially glass, aluminum or magnesium. Using hot water under high pressure (1,000 psi or higher), rinse surface completely.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.

Technical Specifications

Appearance	White Powder
Odor	Characteristic
pH (1% solution, 22°C)	>11.0
Foaming	Very High
Flash Point	N/A
Bulk Density (lbs/gal, 22°C)	9.00±0.1
Stability Range	N/A
Free Alkalinity (as Na ₂ O)	High
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content (as P)	<12.0%

Product Number

81850
81801
81803

Packaging

50 lb. drum
100 lb. drum
300 lb. drum



4701 W. 136th St. • Crestwood, IL 60418
tel (708) 371-6990 • (800) 672-4065
fax (708) 371-6992
www.crown-chem.com

