

KILL FOAM™

Foam Eliminator for Carpet Extraction and Other Applications

Professional quality silicone defoamer for rapid and complete elimination of foam in many applications. Ideal for use in the recovery tank of a carpet extraction machine. Also suitable for parts washing machines, machine dishwashing, and a variety of other applications where unwanted foam must be removed. Special formula immediately attacks and destroys unwanted foam. Helps to assure proper equipment operation and reduces incidents of motor damage. Contains silicone - not recommended for use where parts will be painted or treated.

Directions for Use

Use 1-2 ounces per 10 gallons of solution to be treated. Agitate solution as needed to facilitate dispersion of this product in solution. Foam will normally be eliminated immediately. Adjust quantity as required by individual circumstances.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's can be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	White Liquid
Odor	Characteristic
pH (1% solution, 22°C)	<8.0
Foaming	None
Flash Point	None
Bulk Density (lbs/gal, 22°C)	8.30 ±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	None
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

53141

Packaging

4x1 gal. case