



CROWN™

Technical Data Sheet

SEAL DRY™



Clear-Coat Scented Sealer for Faster Drying & Spot-Free Shine for Brush, Manual, & Tunnel Car Washes

Clear coat scented sealer which enhances the appearance of all vehicles. Designed for high pressure application, but may be used with low pressure as well. Excellent for application by itself or following the use of triple foam polish or triple foam conditioner. Improves shine and speeds up drying. Pleasant fragrance.

Directions for Use

The amount of this product to use will depend on several variables, including conveyor speed, temperature, drip area, etc. For optimum drying and waxing performance with minimum product waste, adjust proportioner as recommended by equipment manufacturer, or adjust metering device to give maximum results. Apply full strength at the rate of 192:1 - 250:1 (approximately 1/2 to 2/3 oz. per vehicle). This product may also be prediluted at 20-25:1 in cold water (red or blue Hydrominder tip). For manual drum mixing, add 1-3 gallons into a clean plastic drum, then fill to 55 gallons while stirring. Apply diluted solution at the rate of 2-3 ounces per vehicle. Cold weather may require higher usage amounts.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	Orange Liquid
Odor	Cherry
pH (1% solution, 22°C)	<9.0
Foaming	None
Flash Point	>200°F
Bulk Density (lbs/gal, 22°C)	8.06±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	None
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

84205
84215
84230
84255

Packaging

5 gal. pail
15 gal. drum
30 gal. drum
55 gal. drum



4701 W. 136th St. • Crestwood, IL 60418
tel (708) 371-6990 • (800) 672-4065
fax (708) 371-6992
www.crown-chem.com



★ MADE IN USA ★