



CROWN™

Technical Data Sheet

SPLASH DOWN™



High-Performance Foaming Detergent for Cars & Trucks

for Brush, Manual, & Tunnel Car Washes

The professional's choice for washing all types of automobiles by hand or with foaming applicators. Contains a specially formulated blend of surfactants which produce abundant, long-lasting suds that effectively cut through even the heaviest road film accumulations. This product is pH balanced to be mild to the hands, and will not attack aluminum or glass. Rinses thoroughly. Pleasantly scented. An excellent brush lubricant for tunnel and in-bay car washes.

Directions for Use

This product should be diluted at ¼ - ½ ounce per gallon of warm water for manual washing or automatic dispensing. Heavier soil buildup may require up to 1 ounce per gallon. Apply foaming solution liberally to top of vehicle first, then work downwards. Agitate to facilitate soil removal, then rinse surfaces completely.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.

Technical Specifications

Appearance	Yellow-Green Liquid
Odor	Lemon
pH (1% solution, 22°C)	<8.0
Foaming	Very High
Flash Point	None
Bulk Density (lbs/gal, 22°C)	8.46±0.1
Stability Range	50-100°F
Free Alkalinity (as Na ₂ O)	None
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

82105
82115
82130
82155

Packaging

5 gal. pail
15 gal. drum
30 gal. drum
55 gal. drum



4701 W. 136th St. • Crestwood, IL 60418
tel (708) 371-6990 • (800) 672-4065
fax (708) 371-6992
www.crown-chem.com



★ MADE IN USA ★