

CR∩WNTechnical Data Sheet

STREET FIGHTER



Premium High-Foaming Alkaline Pressure Washing Detergent for Truck Wash & Hard Surface Cleaning

Removes the toughest deposits of road film, grime, exhaust carbon staining and bug residue. Ideal for use in pressure washing applications, but also suitable for "bucket and brush" washing. Fortified with a powerful blend of solvents, alkalis, and surfactants for superb penetration and removal of difficult soils. Ideal for use on trucks, buses, trailers and other transportation equipment. May also be used to clean walls, machinery, equipment and most other hard, non-porous surfaces. High foaming for prolonged vertical cling. Non-fuming and non-flammable. Not recommended for use on aluminum, tin, pewter or other non-ferrous or galvanized metals.

Directions for Use

Pressure Washing: Using low pressure, apply this product at a feed rate of 2-4 ounces per gallon of hot water (30-60:1) depending on soil levels. For best results, apply to a dry surface--do not prewet. Work from the bottom up until all surfaces are thoroughly coated with detergent solution. Allow several minutes contact time for detergent to penetrate and dissolve soils. Using hot water under high pressure (1,000 psi or higher), rinse surface completely. Do not allow solutions to dry on surface.

Manual Washing: Dilute this product at 1-2 ounces per gallon of hot water (60-100:1). Apply using a vehicle brush, scrub, then rinse completely. Not recommended for use in car washes.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance
Odor
pH (1% solution, 22°C)
Foaming
Flash Point
Bulk Density (lbs/gal, 22°C)
Stability Range
Free Alkalinity (as Na₂O)
Solubility (in H₂O, 22°C)
Phosphate Content

Product Number

Blue Liquid Characteristic >11.5 High None 9.48±0.1 50-100°F Very High 100% None

Packaging

5 gal. pail 15 gal. drum 30 gal. drum 55 gal. drum



4701 W. 136th St. • Crestwood, IL 60418 tel (708) 371-6990 • (800) 672-4065 fax (708) 371-6992 www.crown-chem.com

