

TERRASEAL™

Multi-Purpose Sealer for Resilient Floors

A professional quality, semi-permanent base for sealing resilient tile floors. Provides a durable acrylic base for conventional and high speed floor finishes. Fills pores in tile and provides beautiful initial gloss. Recommended for use on floors made of linoleum, vinyl, asbestos, terrazzo, rubber, concrete and unglazed ceramic. Ideal for use in shopping malls, retail stores, office buildings, health clubs, schools, nursing homes, hospitals, etc.

Directions for Use

Before use, pretest this product in an inconspicuous area to assure compatibility with surface. Strip old finish from floor, rinse completely and allow to air dry. Apply this product in thin, even coats using a rayon mop or lambs wool pad. Allow at least 30 minutes drying time before applying floor finish or using floor area.

Coverage = approximately 2,500 sq. ft./gal.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's can be downloaded from www.crown-chem.com.



Technical Specifications

Appearance	White Liquid
Odor	Characteristic
pH (1% solution, 22°C)	<8.0
Foaming	None
Flash Point	None
Bulk Density (lbs/gal, 22°C)	8.33 ±0.1
Stability Range	40-100°F
Free Alkalinity (as Na ₂ O)	None
Solubility (in H ₂ O, 22°C)	100%
Phosphate Content	None

Product Number

44341
44305

Packaging

4x1 gal. case
5 gal. pail