

CRTWNTechnical Data Sheet

TRAILBLAZER[™]



High-Performance Brushless Truck and Trailer Detergent for Painted Surfaces on Commercial Vehicles

A high-performance detergent designed for brushless cleaning of trucks, trailers, buses, automobiles, forklifts, and other commercial vehicles. Designed for use with pressure washing equipment or pump sprayers. Effective with high or low pressure using hot or cold water. Effectively removes road film, exhaust deposits, bug residues and soil buildup quickly and completely. No brushing required. Contains an advanced blend of chelants, alkalis and synergistic surfactants which penetrate road soils and hold them in suspension for free rinsing. High foam levels provide increased contact time on vertical surfaces for improved cleaning performance.

Directions for Use

Prior to use, test this product in an inconspicuous area to assure compatibility with surface. **Preparation of Premix:** Mix 5-10 gallons of this product (depending on soil level) with warm water to make a 55 gallon drum of solution.

Brushless Truck and Trailer Washing: Apply premix at a rate of 2-8 ounces per gallon of water (16:1-64:1 ratio). While this product will work with most water temperatures and pressures, best results will be achieved with hot water (140°-160°F, preferably softened) applied at 1,000 psi or higher. Start by applying solution to dry surface at low pressure, working from the bottom up. Product should not be allowed to dry on surfaces, so do not apply to an area that is too large. Allow several minutes contact time for chemical to penetrate soils. Brush heavy grease or soil accumulations if needed, then rinse completely with hot, high-pressure water.

Safety Reminder

Consult product label and Safety Data Sheet (SDS) before use. SDS's may be downloaded from www.crown-chem.com.



Technical Specifications

Appearance
Odor
pH (1% solution, 22°C)
Foaming
Flash Point
Bulk Density (lbs/gal, 22°C)
Stability Range
Free Alkalinity (as Na₂O)
Solubility (in H₂O, 22°C)
Phosphate Content

Product Number

Colorless Liquid Characteristic >10.0 High None 9.78±0.1 50-100°F Low 100% None

Packaging

5 gal. pail 15 gal. drum 30 gal. drum 55 gal. drum



4701 W. 136th St. • Crestwood, IL 60418 tel (708) 371-6990 • (800) 672-4065 fax (708) 371-6992 www.crown-chem.com

